

### In the Claims

This listing of claims will replace all prior versions and listings of claims in the application:

1        1. (Currently Amended) A data transfer controller comprising:  
2        a request queue controller capable of receiving, prioritizing  
3        and dispatching data transfer requests each specifying a data  
4        source, a data destination and a data quantity to be transferred;  
5        a data transfer hub connected to the request queue controller  
6        for receiving dispatched data transfer requests;  
7        a plurality of ports having an interior interface connected to  
8        the data transfer hub which is so configured as to be the same for  
9        each port and an exterior interface configured for an external  
10       memory/device which, in operation, is connected to said port, the  
11       interior interface and the exterior interface being connected for  
12       data transfer therebetween;  
13       at least one transfer requestor node connected to said request  
14       queue controller and capable of supplying a data transfer request  
15       to said request queue controller;  
16       wherein the data transfer hub being capable of controlling  
17       data transfers from a source port corresponding to the data source  
18       to a destination port corresponding to the data destination in  
19       quantities corresponding to the data quantities to be transferred  
20       under a currently executing data transfer request; and  
21       wherein at least one of said plurality of ports consists of an  
22       active data port connected to said request queue controller capable  
23       of supplying a data transfer request to said request queue  
24       controller specifying a data source, a data destination and a data  
25       quantity to be transferred.

1       2. (Original) The data transfer controller of claim 1,  
2       wherein:

3        said active data port capable of generating a data transfer  
4 request specifying said active data port as said data destination;  
5        wherein said data transfer hub generates a read command to  
6 said data source and transfers read data to said active data port.

1        3.    (Original) The data transfer controller of claim 2,  
2 wherein:

3        said data transfer hub generates a pre-write command to said  
4 active data port prior to transferring said read data to said  
5 active port; and

6        said active data port generates an acknowledge signal to said  
7 data transfer hub following receipt of said pre-write command when  
8 said active data port is ready to receive data.

1        4.    (Original) The data transfer controller of claim 1,  
2 wherein:

3        said active data port capable of generating a data transfer  
4 request specifying said active data port as said data source;

5        wherein said data transfer hub generates a read command to  
6 said active data port and transfers read data to said data  
7 destination.

1        5.    (Original) The data transfer controller of claim 4,  
2 wherein:

3        said interior interface of said active data port supplies a  
4 read data command to said exterior interface of said active data  
5 port in response to read data command of said data transfer hub.

1        6.    (Original) The data transfer controller of claim 4,  
2 wherein:

3        said interior interface of said active data port includes a  
4 first-in-first-out buffer;

5       said exterior interface writing data into said first-in-first-  
6 out buffer upon generation of said data transfer request by said  
7 active data port; and  
8       said interior interface supplying data read from said first-  
9 in-first-out buffer upon receipt of said read command from said  
10 data transfer hub.

1       7. (Original) The data transfer controller of claim 6,  
2 wherein:

3       said interior interface of said active port generates a stall  
4 signal to said exterior interface of said active port when said  
5 first-in-first-out buffer is full; and

6       said exterior interface refrains from writing data into said  
7 first-in-first-out buffer upon receipt of said stall signal.

1       8. (Currently Amended) A method of data transfer comprising  
2 the steps of:

3       generating via at least one transfer requestor node data  
4 transfer requests each specifying a data source, a data destination  
5 and a data quantity to be transferred

6       receiving, prioritizing and dispatching data transfer requests  
7 ~~each specifying a data source, a data destination and a data~~  
8 ~~quantity to be transferred;~~

9       transferring data from a source port selected from a plurality  
10 of ports corresponding to the data source specified in a data  
11 transfer request to a destination port selected from said plurality  
12 of ports corresponding to the data destination specified in the  
13 data transfer request in quantities corresponding to the data  
14 quantities to be transferred specified in the data transfer request  
15 under a currently executing data transfer request;

16       wherein at least one of said plurality of ports is an active  
17 data port ~~capable of;~~ and

18        generating a data transfer request at an active data port  
19 specifying a data source, a data destination and a data quantity to  
20 be transferred.

1        9. (Currently Amended) The method of data transfer of claim  
2 8, wherein:

3        ~~said active data port is capable of~~ generating a data transfer  
4 request at an active data port specifying said active data port as  
5 said data destination.

1        10. (Original) The method data transfer of claim 9, further  
2 comprising the steps of:

3        supplying a pre-write command to said active data port prior  
4 to transferring said read data to said active port; and

5        supplying an acknowledge signal from said active data port  
6 following receipt of said pre-write command when said active data  
7 port is ready to receive data.

1        11. (Currently Amended) The method of data transfer of claim  
2 8, wherein:

3        ~~said active data port is capable of~~ generating a data transfer  
4 request at an active data port specifying said active data port as  
5 said data source.

1        12. (Original) The method of data transfer of claim 11,  
2 further comprising the steps of:

3        writing data into a first-in-first-out buffer upon generation  
4 of said data transfer request by said active data port; and

5        supplying data read from said first-in-first-out buffer upon  
6 receipt of a read command by from said active data port.

1        13. (Original) The method of data transfer of claim 12,  
2 further comprising the steps of:  
3        generating a stall signal when said first-in-first-out buffer  
4 is full; and  
5        refraining from writing data into said first-in-first-out  
6 buffer upon generation of said stall signal.

1        14. (Previously Presented) The data transfer controller of  
2 claim 1, further comprising:  
3        a plurality of transfer request nodes disposed in a chain  
4 having an upstream most node and a downstream most node, said  
5 downstream node connected to said request queue controller;  
6        a plurality of transfer requestor nodes each capable of  
7 generating service requests and each connected to a corresponding  
8 one of said plurality of transfer request nodes; and  
9        a special transfer request node connected to said upstream  
10 most node of said plurality of transfer request nodes and said  
11 active data port, said special transfer request node connecting  
12 said active data port to said request queue controller via said  
13 plurality of transfer request nodes.

1        15. (Currently Amended) The method of data transfer of claim  
2 8, wherein:  
3        said step of receiving, prioritizing and dispatching data  
4 transfer requests is performed by a request queue controller;  
5        further comprising the steps of:  
6        transferring data transfer requests from each of a plurality  
7 of transfer requestor nodes to said request queue controller via a  
8 chain of a plurality of transfer request nodes having an upstream  
9 most node and a downstream most node, said downstream node  
10 connected to said request queue controller; and

11       transferring data transfer requests from said active data port  
12 to said request queue controller via a special transfer request  
13 node connected to said upstream most transfer request node.